

The regulation forecast is subject to change daily as actual events occur.
Forecasted release reductions or increases are subject to change based on forecasted temperature and river conditions
and releases may be adjusted during winter freeze-in period. Intrasystem regulation may also require release adjustments.

REGULATION FORECAST: 09/04/25																														
FTPK					GARR				OAHE				BEND				FTRA				GAPT				SYSTEM					
		24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	GE	SG	DSG		
T	4	2224.1	5.0	9.0	2.93	1832.5	12.2	19.0	5.50	1599.5	21.4	20.0	5.72	1420.7	20.4	23.0	2.56	1355.4	23.8	20.5	4.39	1207.0	22.9	23.5	2.19	23.29	50873	-23	4	T
F	5	2224.1	5.0	9.0	2.93	1832.4	13.0	19.0	5.49	1599.5	21.1	20.0	5.72	1420.6	20.0	23.0	2.56	1355.4	23.2	20.5	4.40	1206.9	22.7	23.5	2.18	23.29	50841	-32	5	F
	6	2224.0	5.0	9.0	2.93	1832.4	13.8	19.0	5.49	1599.5	21.0	18.0	5.16	1420.8	18.4	13.0	1.47	1355.3	15.9	20.5	4.39	1206.9	22.7	23.5	2.18	21.63	50816	-25	6	
	7	2224.0	5.0	9.0	2.93	1832.3	14.0	19.0	5.49	1599.5	21.0	16.0	4.60	1421.0	16.4	10.0	1.14	1355.1	11.8	21.0	4.49	1206.8	22.7	23.5	2.18	20.83	50789	-27	7	
M	8	2223.9	5.0	9.0	2.93	1832.3	13.9	19.0	5.49	1599.5	21.0	20.0	5.72	1420.8	19.2	23.0	2.57	1355.0	19.5	22.0	4.70	1206.7	22.9	23.5	2.18	23.59	50746	-43	8	M
T	9	2223.9	5.0	9.0	2.93	1832.3	13.9	19.0	5.49	1599.5	21.0	20.0	5.72	1420.7	20.0	23.0	2.57	1355.0	21.9	22.0	4.70	1206.7	23.6	23.5	2.18	23.58	50712	-34	9	T
W	10	2223.8	5.0	9.0	2.93	1832.2	13.8	19.0	5.49	1599.5	21.0	20.0	5.72	1420.6	20.0	23.0	2.56	1355.0	23.2	22.0	4.70	1206.8	24.0	23.5	2.18	23.57	50681	-31	10	W
T	11	2223.7	5.0	9.0	2.93	1832.2	13.8	19.0	5.48	1599.5	21.0	20.0	5.72	1420.5	20.0	23.0	2.56	1355.0	23.2	22.0	4.70	1206.8	24.2	23.5	2.18	23.57	50649	-32	11	T
F	12	2223.7	5.0	9.0	2.93	1832.1	13.8	19.0	5.48	1599.5	21.0	20.0	5.72	1420.4	20.0	23.0	2.56	1355.0	23.2	22.5	4.80	1206.9	24.1	23.5	2.18	23.67	50617	-32	12	F
	13	2223.6	5.0	9.0	2.93	1832.1	13.8	19.0	5.48	1599.5	21.0	18.0	5.16	1420.7	18.4	9.5	1.08	1354.8	13.8	22.5	4.80	1206.9	24.4	23.5	2.18	21.63	50595	-22	13	
	14	2223.6	5.0	9.0	2.92	1832.0	13.8	19.0	5.48	1599.5	21.0	16.0	4.60	1421.0	16.4	7.0	0.80	1354.5	9.3	22.5	4.79	1207.0	24.5	24.0	2.23	20.82	50568	-27	14	
M	15	2223.5	5.0	9.0	2.92	1832.0	13.8	16.0	4.63	1599.5	20.9	21.0	6.00	1420.8	20.0	24.0	2.68	1354.4	19.4	22.5	4.78	1207.0	24.6	24.0	2.23	23.24	50529	-39	15	M
T	16	2223.4	5.0	9.0	2.92	1832.0	13.8	14.0	4.06	1599.5	19.7	21.0	6.00	1420.7	21.0	24.0	2.67	1354.4	22.5	22.5	4.78	1207.0	24.6	24.0	2.23	22.67	50500	-29	16	T
W	17	2223.4	5.0	9.0	2.92	1831.9	13.8	14.0	4.06	1599.4	17.8	21.0	6.00	1420.6	21.0	24.0	2.67	1354.4	24.2	22.0	4.68	1207.1	24.6	24.0	2.23	22.56	50474	-26	17	W
T	18	2223.3	5.0	9.0	2.92	1831.9	13.8	14.0	4.06	1599.4	16.5	21.0	6.00	1420.5	21.0	24.0	2.67	1354.4	24.2	22.5	4.78	1207.1	24.3	24.0	2.23	22.66	50442	-32	18	T
F	19	2223.3	5.0	9.0	2.92	1831.9	13.8	14.0	4.06	1599.3	16.1	21.0	5.99	1420.4	21.0	24.0	2.66	1354.5	24.2	23.0	4.88	1207.1	24.4	24.0	2.23	22.76	50407	-35	19	F
	20	2223.2	5.0	9.0	2.92	1831.9	13.8	14.0	4.06	1599.3	16.0	19.0	5.43	1420.7	19.4	10.5	1.19	1354.3	14.8	23.0	4.88	1207.1	24.7	24.5	2.28	20.76	50383	-24	20	
	21	2223.1	5.0	9.0	2.92	1831.9	13.8	14.0	4.06	1599.3	16.0	17.0	4.87	1421.0	17.4	8.0	0.92	1353.9	10.3	23.0	4.87	1207.2	25.0	24.5	2.28	19.91	50354	-29	21	
M	22	2223.1	5.0	9.0	2.92	1831.9	13.7	14.0	4.06	1599.2	15.9	21.0	5.99	1420.8	20.2	24.0	2.68	1353.9	19.7	23.0	4.86	1207.2	25.1	24.5	2.28	22.79	50310	-44	22	M
T	23	2223.0	5.0	9.0	2.92	1831.9	13.7	14.0	4.06	1599.2	15.8	21.0	5.99	1420.7	21.0	24.0	2.67	1353.8	22.6	23.5	4.96	1207.2	25.0	24.5	2.28	22.88	50272	-38	23	T
W	24	2223.0	5.0	9.0	2.91	1831.8	13.7	14.0	4.06	1599.1	15.7	21.0	5.99	1420.6	21.0	24.0	2.67	1353.8	24.2	23.5	4.96	1207.3	25.3	24.5	2.28	22.87	50238	-34	24	W
T	25	2222.9	5.0	9.0	2.91	1831.8	13.7	14.0	4.06	1599.1	15.6	21.0	5.98	1420.5	21.0	24.0	2.67	1353.8	24.2	23.5	4.96	1207.3	25.4	25.0	2.32	22.91	50203	-35	25	T
F	26	2222.9	5.0	9.0	2.91	1831.8	13.7	14.0	4.06	1599.0	15.5	21.0	5.98	1420.4	21.0	24.0	2.66	1353.8	24.2	23.5	4.96	1207.4	25.5	25.0	2.32	22.90	50167	-36	26	F
	27	2222.8	5.0	9.0	2.91	1831.8	13.7	14.0	4.06	1599.0	15.5	19.0	5.42	1420.7	19.4	10.5	1.19	1353.6	14.8	23.5	4.96	1207.4	25.5	25.0	2.33	20.87	50140	-27	27	

Project:	System:	Units:
24EL Midnight Elevation (feet)	GE Daily Power Generation (1000 MWh)	kcfs thousand cubic feet per second
24ID Daily Average Inflow (kcfs)	SG Midnight Storage (kaf)	MWh megawatt hour
240D Daily Average Release (kcfs)	DSG Daily Storage Change (kaf)	kaf thousand acre-feet
24GE Daily Power Generation (1000 MWh)		

The midnight elevation (24EL) will be shown in color when a reservoir enters one of the following zones.
1234.5 Exclusive Flood Control Zone (24EL)
1234.5 Surcharge Zone (24EL)

The daily average release (240D) will be shown in color when a project's releases exceed the available power plant capacity.
34.5

Elevation shown in Local Project Datum (LPD)