

The regulation forecast is subject to change daily as actual events occur.
Forecasted release reductions or increases are subject to change based on forecasted temperature and river conditions
and releases may be adjusted during winter freeze-in period. Intrasystem regulation may also require release adjustments.

REGULATION FORECAST: 02/04/26																															
FTPK					GARR				OAHE				BEND				FTRA				GAPT				SYSTEM						
		24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	24EL	24ID	240D	24GE	GE	SG	DSG			
W	4	2221.8	6.6	5.0	1.61	1827.8	12.3	16.0	4.52	1601.2	16.9	17.0	4.94	1420.7	16.9	20.0	2.24	1344.8	20.9	12.0	2.39	1206.1	14.0	14.0	1.32	17.02	48769	13	4	W	
T	5	2221.8	6.3	5.0	1.61	1827.7	11.8	16.0	4.52	1601.2	17.1	17.0	4.94	1420.6	17.0	20.0	2.24	1345.0	21.1	12.0	2.40	1206.1	14.0	14.0	1.32	17.02	48776	7	5	T	
F	6	2221.8	6.1	5.0	1.61	1827.7	11.4	16.0	4.52	1601.2	17.3	17.0	4.94	1420.5	17.0	20.0	2.23	1345.4	21.2	10.0	2.01	1206.3	14.2	12.0	1.14	16.45	48790	14	6	F	
	7	2221.8	5.8	5.0	1.61	1827.7	10.9	16.0	4.52	1601.2	17.4	15.0	4.37	1420.7	15.4	8.0	0.91	1345.4	12.8	10.0	2.01	1206.4	13.2	12.0	1.14	14.56	48808	18	7		
	8	2221.9	5.6	5.0	1.61	1827.6	10.5	16.0	4.51	1601.3	17.6	13.0	3.80	1421.0	13.4	6.0	0.69	1345.4	9.0	10.0	2.01	1206.4	12.4	12.0	1.14	13.77	48821	13	8		
M	9	2221.9	5.5	5.0	1.61	1827.6	10.2	16.0	4.51	1601.3	17.7	17.0	4.94	1420.9	16.2	20.0	2.24	1345.6	17.2	10.0	2.01	1206.4	12.0	12.0	1.14	16.47	48818	-3	9	M	
T	10	2221.9	5.5	5.0	1.61	1827.5	10.0	16.0	4.51	1601.3	17.7	17.0	4.94	1420.8	17.0	20.0	2.24	1345.9	19.8	10.0	2.02	1206.4	11.9	12.0	1.14	16.47	48821	3	10	T	
W	11	2221.9	5.5	5.0	1.61	1827.5	9.9	16.0	4.51	1601.3	17.7	17.0	4.95	1420.7	17.0	20.0	2.24	1346.2	21.2	10.0	2.02	1206.4	11.9	12.0	1.14	16.47	48827	6	11	W	
T	12	2221.9	5.5	5.0	1.61	1827.5	9.8	16.0	4.51	1601.3	17.7	17.0	4.95	1420.6	17.0	20.0	2.24	1346.5	21.2	10.0	2.03	1206.4	11.8	12.0	1.14	16.47	48834	7	12	T	
F	13	2221.9	5.5	5.0	1.63	1827.4	9.8	16.0	4.51	1601.3	17.7	17.0	4.95	1420.5	17.0	20.0	2.23	1346.9	21.2	10.0	2.04	1206.4	11.8	12.0	1.14	16.49	48839	5	13	F	
	14	2221.9	5.5	5.0	1.63	1827.4	9.7	16.0	4.51	1601.3	17.7	15.0	4.37	1420.7	15.4	7.5	0.86	1346.9	12.4	10.0	2.04	1206.3	11.8	12.0	1.14	14.54	48852	13	14		
	15	2221.9	5.5	5.0	1.63	1827.3	9.7	16.0	4.51	1601.3	17.7	13.0	3.80	1421.0	13.4	5.5	0.63	1346.9	8.5	10.0	2.04	1206.3	11.8	12.0	1.14	13.74	48861	9	15		
M	16	2221.9	5.5	5.0	1.63	1827.3	9.7	16.0	4.50	1601.3	17.7	17.0	4.95	1420.9	16.2	20.0	2.24	1347.1	17.0	10.0	2.04	1206.3	11.8	12.0	1.14	16.50	48858	-3	16	M	
T	17	2221.9	5.5	5.0	1.63	1827.2	9.7	16.0	4.50	1601.3	17.7	17.0	4.95	1420.8	17.0	20.0	2.24	1347.4	19.7	10.0	2.05	1206.3	11.8	12.0	1.14	16.50	48861	3	17	T	
W	18	2221.9	5.5	5.0	1.63	1827.2	9.7	16.0	4.50	1601.3	17.7	17.0	4.95	1420.7	17.0	20.0	2.24	1347.7	21.2	10.0	2.05	1206.3	11.8	12.0	1.14	16.50	48866	5	18	W	
T	19	2221.9	5.5	5.0	1.63	1827.1	9.7	16.0	4.50	1601.3	17.7	17.0	4.95	1420.6	17.0	20.0	2.24	1348.0	21.2	10.0	2.06	1206.3	11.8	12.0	1.14	16.50	48870	4	19	T	
F	20	2221.9	5.5	5.0	1.63	1827.1	9.7	16.0	4.50	1601.3	17.7	17.0	4.95	1420.5	17.0	20.0	2.23	1348.3	21.2	10.0	2.06	1206.2	11.8	12.0	1.14	16.50	48876	6	20	F	
	21	2221.9	5.5	5.0	1.63	1827.0	9.7	16.0	4.50	1601.4	17.7	15.0	4.38	1420.7	15.4	7.5	0.86	1348.3	12.4	10.0	2.06	1206.2	11.8	12.0	1.14	14.56	48889	13	21		
	22	2221.9	5.5	5.0	1.63	1827.0	9.6	16.0	4.50	1601.4	17.7	13.0	3.80	1421.0	13.4	5.0	0.58	1348.3	8.2	10.0	2.06	1206.2	11.8	12.0	1.14	13.70	48898	9	22		
M	23	2221.9	5.5	5.0	1.63	1826.9	9.6	16.0	4.49	1601.4	17.7	17.5	5.09	1420.9	16.6	20.5	2.30	1348.5	17.3	10.0	2.06	1206.2	11.8	12.0	1.14	16.71	48894	-4	23	M	
T	24	2221.9	5.5	5.0	1.63	1826.9	9.6	16.0	4.49	1601.4	17.7	17.5	5.09	1420.8	17.5	20.5	2.29	1348.8	20.1	10.0	2.07	1206.2	11.8	12.0	1.14	16.71	48895	1	24	T	
W	25	2221.9	5.5	5.0	1.63	1826.9	9.6	16.0	4.49	1601.4	17.7	17.5	5.09	1420.7	17.5	20.5	2.29	1349.1	21.7	10.0	2.07	1206.2	11.8	12.0	1.14	16.71	48902	7	25	W	
T	26	2221.9	5.5	5.0	1.63	1826.8	10.1	16.0	4.49	1601.4	18.2	17.5	5.09	1420.6	17.5	20.5	2.29	1349.4	21.7	10.0	2.08	1206.1	11.8	12.0	1.14	16.71	48909	7	26	T	
F	27	2222.0	5.5	5.0	1.63	1826.8	10.5	16.0	4.49	1601.4	18.6	17.5	5.09	1420.5	17.5	20.5	2.29	1349.7	21.7	10.0	2.08	1206.1	11.8	12.0	1.14	16.71	48918	9	27	F	

Project:	System:	Units:
24EL Midnight Elevation (feet)	GE Daily Power Generation (1000 MWh)	kcfs thousand cubic feet per second
24ID Daily Average Inflow (kcfs)	SG Midnight Storage (kaf)	MWh megawatt hour
240D Daily Average Release (kcfs)	DSG Daily Storage Change (kaf)	kaf thousand acre-feet
24GE Daily Power Generation (1000 MWh)		

The midnight elevation (24EL) will be shown in color when a reservoir enters one of the following zones.
1234.5 Exclusive Flood Control Zone (24EL)
1234.5 Surcharge Zone (24EL)

The daily average release (240D) will be shown in color when a project's releases exceed the available power plant capacity.
34.5

Elevation shown in Local Project Datum (LPD)